



20' OR 24'
CURB & GUTTER
PAVING

NOTE:

1. SOIL ANALYSIS MAY INDICATE THE NEED FOR THICKER BASE COURSES THAN THOSE SHOWN HEREIN. THE PAVEMENT THICKNESS SHOWN HEREIN ARE NOT INTENDED TO BE ABSOLUTE, BUT ARE PRELIMINARY CRITERIA & MAY BE MODIFIED TO ACCOMMODATE THE BEARING CAPACITIES OF VARIOUS SUBGRADES.
 2. ALL DISTURBED AREAS SHALL BE SEEDED & MULCHED. ALL AREAS WHERE SOD HAS BEEN DISTURBED OR REMOVED SHALL BE RESEEDDED TO SATISFACTION OF OWNER.
 3. ALL ASPHALTIC CONCRETE SHALL MEET THE REQUIREMENTS OF SECTION 331 AND/OR SECTION 333, F.D.O.T. STANDARD SPECIFICATIONS, LATEST EDITION.
- *. OR IN ACCORDANCE WITH APPROVED CONSTRUCTION PLANS. VARIATIONS IN SIDEWALK LOCATION/ MEANDERING DUE TO CONFLICTS SUCH AS TREES, HYDRANTS, UTILITIES, TRAFFIC SIGN, ETC. IS PERMITTED AS PER THE APPROVED PLANS, OR AS OTHERWISE REQUIRED TO BE ADJUSTED IN THE FIELD.

RESIDENTIAL
50' R/W MIN.
URBAN

CITY OF
JACKSONVILLE
STANDARD

N.T.S.	PLATE P-102
DATE DRAWN	2-24-89
REVISED DATE	03/18/04