



1-1/2" ASPHALTIC CONCRETE TYPE S-I
OR S-III 1500 L.B. MARSHALL

8" COMPACTED LIMEROCK BASE MIN. L.B.R. 75,
100% MAX. DENSITY A.A.S.H.T.O. T-180

12" CONSTRUCTED SUB-BASE MIN. L.B.R. 40,
MAX. PLASTIC INDEX OF 6, COMPACTED
TO 98% MAX. DENSITY A.A.S.H.T.O. T-180

CURB & GUTTER
24' PAVING

NOTE:

1. SOIL ANALYSIS MAY INDICATE THE NEED FOR THICKER BASE COURSES THAN THOSE SHOWN HEREIN. THE PAVEMENT THICKNESS SHOWN HEREIN ARE NOT INTENDED TO BE ABSOLUTE, BUT ARE PRELIMINARY CRITERIA & MAY BE MODIFIED TO ACCOMMODATE THE BEARING CAPACITIES OF VARIOUS SUBGRADES.
 2. ALL DISTURBED AREAS SHALL BE SEEDED & MULCHED. ALL AREAS WHERE SOD HAS BEEN DISTURBED OR REMOVED SHALL BE RESEDDED TO SATISFACTION OF OWNER.
 3. ALL ASPHALTIC CONCRETE SHALL MEET THE REQUIREMENTS OF SECTION 331, F.D.O.T. STANDARD SPECIFICATIONS, LATEST EDITION.
- *. OR IN ACCORDANCE WITH APPROVED CONSTRUCTION PLANS.

INDUSTRIAL
60' R/W MIN.

*CITY OF
JACKSONVILLE
STANDARD*

N.T.S.	PLATE P-104
DATE DRAWN	3-7-89
REVISED DATE	9/5/03