



- 3" ASPHALTIC CONCRETE TYPE S-1 OR S-III 1500 L.B. MARSHALL
- 8" COMPACTED LIMEROCK BASE MIN. L.B.R. 75 100% MAX. DENSITY A.A.S.H.T.O. T-180
- 12" CONSTRUCTED SUB-BASE MIN. L.B.R. 40, MAX. PLASTIC INDEX OF 6, COMPACTED TO 98% MAX. DENSITY A.A.S.H.T.O. T-180

**CURB & GUTTER
75' PAVING**

NOTE:

1. SOIL ANALYSIS MAY INDICATE THE NEED FOR THICKER BASE COURSES THAN THOSE SHOWN HEREIN. THE PAVEMENT THICKNESS SHOWN HEREIN ARE NOT INTENDED TO BE ABSOLUTE, BUT ARE PRELIMINARY CRITERIA & MAY BE MODIFIED TO ACCOMMODATE THE BEARING CAPACITIES OF VARIOUS SUBGRADES.
2. ALL DISTURBED AREAS SHALL BE SEEDED & MULCHED. ALL AREAS WHERE SOD HAS BEEN DISTURBED OR REMOVED SHALL BE RESODED TO SATISFACTION OF OWNER.
3. ALL ASPHALTIC CONCRETE SHALL MEET THE REQUIREMENTS OF SECTION 331, F.D.O.T. STANDARD SPECIFICATIONS, LATEST EDITION.

ARTERIAL
120' R/W MIN.

*CITY OF
JACKSONVILLE
STANDARD*

N.T.S.

PLATE P-108

DATE DRAWN 3-21-89

REVISED DATE 10-8-97